

PERFECT COVER® EXTRA STRONG



DESCRIPTION:

Perfect Cover® Extra Strong is a 3-layer product with a self-adhesive underside, specially developed for covering prefabricated elements and projects where extra strong floor protection is required. This product offers optimal protection against moisture and mechanical damage throughout the entire construction phase. The top side is equipped with a highly absorbent fleece, while the underside has a self-adhesive PE film with an anti-slip coating. This ensures the fleece stays in place during painting and covering work without the need for additional fixing.

Application: The substrate must remain dry, clean, dust-free, and free from chemical agents. It is advisable to conduct preliminary tests. Lay the rolls with an overlap of approximately 4 inches (10 cm) and press firmly. Processing temperature should be between 41°F and 104°F (5-40 °C). Not suitable for recently laid concrete. The underfloor heating must be switched off.

APPLICATION

- Regular Floors
- Stainless steel
- Stairs
- Elevators
- Cabinets
- Glass

FEATURES

- Self-adhesive
- Shock-absorbing
- Moisture resistant
- Reusable
- Anti-slip



TECHNICAL DATA

Appearance	TL.014	-
Width	TL.013	39.37 in (100 cm)
Weight	TS EN 29073-1	1.147 oz/sq. ft. (350 g/m ²)
Thickness	TS EN 29073-2	> 78.74 mils (> 2 mm)
Tensile strength (CD)	TS EN 29073-3	lbf/in 11.42 (N/5cm 100)
Tensile elongation (CD)	TS EN 29073-3	100% (+/- 10%)
Tensile strength (MD)	TS EN 29073-3	lbf/in 11.42 (N/5cm 100)
Tensile elongation (MD)	TS EN 29073-3	80% (+/-20%)
Water vapour permeability	ASTM E398	N.A.
Tearing strength (CD)	TS EN ISO 90732-4	> 102.8 lbf/in (> 900 N/5 cm)
Tearing strength (MD)	TS EN ISO 90732-4	> 131.4 lbf/in (> 1150 N/5 cm)
Peeling at 180	D41 1015	

MATERIAL

- Material - Top layer is viscose with non-woven made of polypropylene
- Adhesive - Dispersion acrylics
- Color - Grey
- Laminated - Laminated

